



## 1A LOW DROPOUT LINEAR REGULATOR

AZ1117

## General Description

The AZ1117 is a series of low dropout three-terminal regulators with a dropout of 1.15V at 1A output current capability.

The AZ1117 has an adjustable version, that can provide the output voltage from 1.25V to 12V with only 2 external resistors.

The AZ1117 series provides current limiting and thermal shutdown. Its circuit includes a trimmed bandgap reference to assure output voltage accuracy to be within 1%. Current limit is trimmed to ensure specified output current and controlled short-circuit current. On-chip thermal limiting provides protection against any combination of overload and ambient temperature that would create excessive junction temperature.

The AZ1117 series is available in the industry standard SOT-223, SOT-89, TO-220, TO-252 and TO-263 power packages.

## Features

- Low dropout voltage: 1.15V at 1A output current
- Trimmed current limit
- On-chip thermal limiting
- Standard SOT-223, SOT-89, TO-220, TO-252 and TO-263 packages
- Three-terminal adjustable or fixed 1.5V, 1.8V, 2.5V, 3.3V, 5V
- Current limit and thermal protection
- Operation junction temp.: 0°C to 125°C

## Applications

- PC Motherboard
- LCD Monitor
- Graphic Card
- DVD-Video Player
- NIC / Switch
- Telecom Equipment
- High Efficiency Linear Regulator
- Printer and other Peripheral Equipment




Figure 1. Package Types of AZ1117



## 1A LOW DROPOUT LINEAR REGULATOR

AZ1117

## Pin Configuration





Figure 2. Pin Configuration of AZ1117



## 1A LOW DROPOUT LINEAR REGULATOR

AZ1117

## Functional Block Diagram





## 1A LOW DROPOUT LINEAR REGULATOR

AZ1117

## Ordering Information

Package	Temperature Range	Part Number	Marking ID	Packing Type
SOT-223	0°C~125°C	AZ1117H-ADJ	H11A	Tape/Reel
		AZ1117H-1.5	H12A	Tape/Reel
		AZ1117H-1.8	H13A	Tape/Reel
		AZ1117H-2.5	H14A	Tape/Reel
		AZ1117H-3.3	H16A	Tape/Reel
		AZ1117H-5.0	H17A	Tape/Reel
SOT-89	0°C~125°C	AZ1117R-ADJ	R17A	Tape/Reel
		AZ1117R-1.5	R17B	Tape/Reel
		AZ1117R-1.8	R17C	Tape/Reel
		AZ1117R-2.5	R17D	Tape/Reel
		AZ1117R-3.3	R17E	Tape/Reel
		AZ1117R-5.0	R17F	Tape/Reel
TO-220	0°C~125°C	AZ1117T-ADJ	AZ1117T-ADJ	Tube
		AZ1117T-1.5	AZ1117T-1.5	Tube
		AZ1117T-1.8	AZ1117T-1.8	Tube
		AZ1117T-2.5	AZ1117T-2.5	Tube
		AZ1117T-3.3	AZ1117T-3.3	Tube
		AZ1117T-5.0	AZ1117T-5.0	Tube
TO-252	0°C~125°C	AZ1117D-ADJ	AZ1117D-ADJ	Tape/Reel
		AZ1117D-1.5	AZ1117D-1.5	Tape/Reel
		AZ1117D-1.8	AZ1117D-1.8	Tape/Reel
		AZ1117D-2.5	AZ1117D-2.5	Tape/Reel
		AZ1117D-3.3	AZ1117D-3.3	Tape/Reel
		AZ1117D-5.0	AZ1117D-5.0	Tape/Reel
TO-263	0°C~125°C	AZ1117S-ADJ	AZ1117S-ADJ	Tape/Reel
		AZ1117S-1.5	AZ1117S-1.5	Tape/Reel
		AZ1117S-1.8	AZ1117S-1.8	Tape/Reel
		AZ1117-2.5	AZ1117-2.5	Tape/Reel
		AZ1117-3.3	AZ1117-3.3	Tape/Reel
		AZ1117-5.0	AZ1117-5.0	Tape/Reel



## 1A LOW DROPOUT LINEAR REGULATOR

AZ1117

**Absolute Maximum Ratings (Note 1)**

Parameter	Value	Unit
V <sub>IN</sub>	20	V
Operating Junction Temperature Range	150	°C
Storage Temperature Range	-65 ~ 150	°C
Lead Temperature (Soldering, 10 sec.)	300	°C
ESD (Machine Model)	600	V

Note 1: Stresses greater than those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "Recommended Operation Ratings" is not implied. Exposure to "Absolute Maximum Ratings" for extended periods may affect device reliability.

**Recommended Operating Ratings**

Parameter	Min	Max	Unit
V <sub>IN</sub>		15	V
Operating Junction Temperature Range	0	125	°C
Storage Temperature Range	-65	150	°C



## 1A LOW DROPOUT LINEAR REGULATOR

AZ1117

**Electrical Characteristics**(Typicals and limits apply for  $T_J = 25^\circ\text{C}$  unless otherwise specified.)

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Reference Voltage	$V_{\text{REF}}$	$V_{\text{IN}} - V_{\text{OUT}} = 2\text{V}$ , $T_J = 25^\circ\text{C}$ $10\text{mA} \leq I_{\text{OUT}} \leq 1\text{A}$ , $1.4\text{V} \leq (V_{\text{IN}} - V_{\text{OUT}}) \leq 10\text{V}$	1.238	1.250	1.263	V
Output Voltage	$V_{\text{OUT}}$	AZ1117-1.5, $T_J = 25^\circ\text{C}$ , $0 \leq I_{\text{OUT}} \leq 1\text{A}$ , $3\text{V} \leq V_{\text{IN}} \leq 8\text{V}$	1.485	1.5	1.515	V
		AZ1117-1.8, $T_J = 25^\circ\text{C}$ , $0 \leq I_{\text{OUT}} \leq 1\text{A}$ , $3.2\text{V} \leq V_{\text{IN}} \leq 10\text{V}$	1.782	1.8	1.818	V
		AZ1117-2.5, $T_J = 25^\circ\text{C}$ , $0 \leq I_{\text{OUT}} \leq 1\text{A}$ , $3.9\text{V} \leq V_{\text{IN}} \leq 10\text{V}$	2.475	2.5	2.525	V
		AZ1117-3.3, $T_J = 25^\circ\text{C}$ , $0 \leq I_{\text{OUT}} \leq 1\text{A}$ , $4.75\text{V} \leq V_{\text{IN}} \leq 10\text{V}$	3.267	3.3	3.33	V
		AZ1117-5.0, $T_J = 25^\circ\text{C}$ , $0 \leq I_{\text{OUT}} \leq 1\text{A}$ , $6.5\text{V} \leq V_{\text{IN}} \leq 12\text{V}$	4.95	5.0	5.05	V
Line Regulation	$S_V$	$I_{\text{OUT}} = 10\text{mA}$ , $1.5\text{V} \leq V_{\text{IN}} - V_{\text{OUT}} \leq 10\text{V}$		0.035		%
Load Regulation	$S_I$	$V_{\text{IN}} - V_{\text{OUT}} = 2\text{V}$ , $10\text{mA} \leq I_{\text{OUT}} \leq 1\text{A}$		0.15		%
Dropout Voltage	$\Delta V$	$I_{\text{OUT}} = 100\text{mA}$		1.00	1.1	V
		$I_{\text{OUT}} = 500\text{mA}$		1.08	1.18	V
		$I_{\text{OUT}} = 1\text{A}$		1.15	1.25	V
Current Limit	$I_{\text{limit}}$	$(V_{\text{IN}} - V_{\text{OUT}}) = 2\text{V}$		1.50		A
Adjust Pin Current				60		$\mu\text{A}$
Adjust Pin Current Change		$1.4\text{V} \leq (V_{\text{IN}} - V_{\text{OUT}}) \leq 7\text{V}$ , $10\text{mA} \leq I_{\text{OUT}} \leq 1\text{A}$		0.2		$\mu\text{A}$
Minimum Load Current (ADJ)		$1.5\text{V} \leq (V_{\text{IN}} - V_{\text{OUT}}) \leq 15\text{V}$		2		mA
Quiescent Current		$V_{\text{IN}} = V_{\text{OUT}} + 1.25\text{V}$		5		mA
Ripple Rejection		$f = 120\text{Hz}$ , $C_{\text{OUT}} = 22\mu\text{F}$ Tantalum, $(V_{\text{IN}} - V_{\text{OUT}}) = 3\text{V}$ , $I_{\text{OUT}} = 1\text{A}$	60	75		dB
Temperature Stability				0.5		%
Long-Term Stability		$A = 125^\circ\text{C}$ , 1000hrs		0.3		%
RMS Output Noise(% of $V_{\text{OUT}}$ )		$T_A = 25^\circ\text{C}$ , $10\text{Hz} \leq f \leq 10\text{kHz}$		0.003		%
Thermal Resistance, Junction to Case		SOT-223 TO-252 TO-220		15 10 4.5		$^\circ\text{C}/\text{W}$
Thermal Shutdown		Junction Temperature		150		$^\circ\text{C}$
Thermal Shutdown Hysteresis				25		$^\circ\text{C}$



## 1A LOW DROPOUT LINEAR REGULATOR

AZ1117

## Typical Characteristics




Figure 4. Dropout Voltage vs. Output Current




Figure 5. Load Regulation vs. Temperature




Figure 6. Reference Voltage vs. Temperature




Figure 7. Output Voltage vs. Temperature



## 1A LOW DROPOUT LINEAR REGULATOR

AZ1117

## Typical Characteristics (Continued)




Figure 8. Minimum Load Current vs. Temperature




Figure 9. Adjust Pin Current vs. Temperature




Figure 10. Short-Circuit Current vs. Temperature




Figure 11. Maximum Power Dissipation



## 1A LOW DROPOUT LINEAR REGULATOR

AZ1117

## Typical Characteristics (Continued)





Figure 12. Line Transient Response

Figure 13. Load Transient Response




Figure 14. Ripple Rejection vs. Frequency



## 1A LOW DROPOUT LINEAR REGULATOR

AZ1117

## Typical Applications




Figure 15. Typical Applications of AZ1117




## 1A LOW DROPOUT LINEAR REGULATOR

AZ1117

## Mechanical Dimensions

SOT - 223






## 1A LOW DROPOUT LINEAR REGULATOR

AZ1117

## Mechanical Dimensions (Continued)

SOT-89






## 1A LOW DROPOUT LINEAR REGULATOR

AZ1117

## Mechanical Dimensions (Continued)

TO - 252






## 1A LOW DROPOUT LINEAR REGULATOR

AZ1117

## Mechanical Dimensions (Continued)

TO - 220






## 1A LOW DROPOUT LINEAR REGULATOR

AZ1117

## Mechanical Dimensions (Continued)

TO - 263





**<http://www.aacmicro.com>**

---

**USA:** 1510 Montague Expressway, San Jose, CA 95131, USA

Tel: 408-433 9888, Fax: 408-432 9888

**China:** 8th Floor, Zone B, 900 Yi Shan Road, Shanghai 200233, China

Tel: 86-21-6495 9539, Fax: 86-21-6485 9673

**Taiwan:** Room 2210, 22nd Fl, 333, Keelung Road, Secretary 1, Taipei, Taiwan Tel: 886-2-2564 3699, Fax: 886-2-2564 3770

#### **IMPORTANT NOTICE**

Advanced Analog Circuits Corporation reserves the right to make changes to its products or specifications at any time, without notice, to improve design or performance and to supply the best possible product. Advanced Analog Circuits does not assume any responsibility for use of any circuitry described other than the circuitry embodied in Advanced Analog Circuits' products. The company makes no representation that circuitry described herein is free from patent infringement or other rights of Advanced Analog Circuits Corporation.