



L1	0.6	BEAD 105
L2	0.6	BEAD 105

	NORMAL	TWO STEP
JN8	X	P-250
J59	0.8	X
J64	0.8	X
J65	0.8	X

* Please refer to tables

	115V	230V
C23	22uF/50V	10uF/100V
C24	4700pF/250V(Y)	X
C25	4700pF/250V(Y)	X
C45	0.33uF/250V(X)	0.1uF/250V(X)
F2	0.1/1W	X 0.1/1W
JP4	0	X
L3	LS-310T	LS-310T
R26	75K/0.25W	200K/0.25W
R27	10K/0.25W	27K/0.25W
R52	100K/0.25W 1%	200K/0.25W 1%
R53	10K/0.25W	27K/0.25W
R73	94.1K/0.25W 1%	200K/0.25W 1%
R121	390.5W	1.5K/5W
R140	94.1K/0.25W 1%	200K/0.25W 1%
R141	100K/0.25W 1%	200K/0.25W 1%
RV1	20D471K	X 20D471K
RV2	20D471K	X 20D471K
RV3	20D271K	14D471K

J30	0.8	X	X
J31	0.8	X	X
J32	0.8	X	X
J33	0.8	X	X
J34	0.8	X	X
J35	0.8	X	X
RY1	X	888H-1A 110VAC	888H-1A 220VAC
RY2	X	888H-1A 110VAC	888H-1A 220VAC

	AC START	
	115V	230V
D9	X	1N4007
R13	X	200K/0.25W
R16	X	330K/0.25W 680K/0.25W
ZD1	X	30-3

POWERCOM CO., LTD					
MODEL	BNT-2000L / 3000 VA (5 LED) (BNT-201,2oz)				
SCH. NO.	D:\PROTEL\BNT\BNT-201\B201V10D.SCH	SIZE	A2		
SHEET	1 OF 1	REV.	1.0	VER.	1.0
DATA	24-Sep-2009	APPROVER		CHECK	
		DESIGN			