



CIRCUIT SYMBOLS			
CAPACITOR		RESISTOR	
	CERAMIC		MYLAR
	NON-POLAR		METALLIZED POLYESTER
	ELECTROLYTIC		POLYESTER FILM
	N.P.O		POLYPROPYLENE
	TANTALUM		METAL PAPER
	CARBON FILM		CEMENT
	METER OXIDE		FUSEABLE
	CARBON COMPOSITION		

NOTE:
 1. ALL CAPACITORS ARE IN uF UNLESS OTHERWISE NOTED.
 2. ALL CAPACITORS ARE 50V UNLESS OTHERWISE NOTED.
 3. ALL RESISTORS ARE IN OHM 1/8 WATT UNLESS OTHERWISE NOTED.
 4. DC VOLTAGE ARE MEASURED FROM POINTS INDICATED TO THE CIRCUIT GROUND WITH A DIGITAL MULTIMETER TEST.
 5. WAVEFORMS ARE TAKEN WITH SETTING CONTROLS TO A NORMAL CONDITIONS (COLOR PHILIPS PATTERN UHF).
 6. THIS CIRCUIT DIAGRAM IS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE.
 7. SAFETY CRITICAL DEVICE.
 8. REMARK "*" MEANS THE VALUE FOR REFERENCE.

ZHONGSHAN KAWA ELECTRONIC RESEARCH & DEVELOPMENT CENTRE
 CTV AUDIO OTHERS
 TITLE : SCHEMATIC DIAGRAM [INITIAL MODEL: LA768B(MONO)] PAPER SIZE: A3
 DWG. NO.: A315-004 | REV.: 00 | DATE: 10-10-2005 | PAGE: 1 OF 1
 FILE NAME: | DRAWN BY: | CHECKED BY: | APPROVED BY: